

Ball flowmeters

Oxyll®



L/min	SS8752430	BS 5682	NF 90 116	Oxifar	DIN 13260
O₂					
0-15 Rail	5540000 5450001	5540002 5450002	5540003 5450004	5540005 5450006	5540006 5450007
0-15 dual Rail	5540050 5450051	5540052 5450052	5540053 5450054	5540055 5450056	5540056 5450057
0-15 selector Rail	5540600 5450601	5540602 5450602	5540603 5450604	5540605 5450606	5540606 5450607
0-15 selector dual Rail	5540620 5450621	5540622 5450622	5540623 5450624	5540625 5450626	5540626 5450627
Air					
0-15 Rail	5540300 5450311	5540302 5450312	5540303 5450314	5540305 5450316	5540306 5450317
0-15 dual Rail	5540350 5450301	5540352 5450302	5540353 5450304	5540355 5450306	5540356 5450307
0-15 selector Rail	5540650 5450631	5540652 5450632	5540653 5450634	5540655 5450636	5540656 5450637
0-15 selector dual Rail	5540640 5450641	5540642 5450642	5540643 5450644	5540645 5450646	5540646 5450647

Special connections available on request.Consult.

DISS	CHEMETRON	OHMEDA	PURITAN	UNI	AFROX	ENV 737-6

Accessories

	Selector piece. Device that can be adapted to any flowmeter with DISS output 9/16"-18 UNF. With a simple twist, select the flow output through the humidifier or through the plug to connect masks or nebulizers.		4540610
	Sterile humidifier. Bubble type with diffuser, autoclave sterilizable at 121 °C. Polycarbonate bottle and polyamide cap. Capacity: 350 mL. Sterilizable humidifier with over-pressure valvule. Bubble type, with diffuser and pressure relief valve, autoclave sterilizable at 121 °C. Polycarbonate bottle and polyamide cap. Capacity: 350 mL.		5530000 5530002
	DISS connector 9/16"-18 UNF metal for O ₂ pipe. DISS 9/16"-18 UNF plastic connector for O ₂ pipe.		4905400 0520101
	O ₂ mask for a single patient.	Adult Child	3210221 3210220
	O ₂ nasal cannula for a single patient.		0930001
	O ₂ mask with nabilizer for a single patient.	Adult Child	0930005 0930006
	O ₂ mask with different concentrations for a single patient.		0930013
	Rail-coupling system for flowmeters, with pipe connection (the type of connection must be specified by the client). Consult.		4450050

Flowmeters

Oxyll®



Exactly
Highly efficient
Easy to handle
Light



Perflow®

ANNIVERSARY
HERSILL 50

FROM THE IDEA
TO THE PATIENT

Puerto de Navacerrada, 3
28935 Mostoles
Madrid, SPAIN

Tel.: +34 91 616 6000
info@hersill.com
www.hersill.com

Standards: ISO 15002:2008



Brochure No.
EN-4540/24-07

Oxyl[®]

These flowmeters are able to compensate for variations of pressure of the piping as they support all the pressure of line, maintain pressure and supply the patient with selected flow rate, at atmospheric pressure, by means of the face mask, nasal cannula, nebulizer, humidifier, etc...

Its scale design allows visibility of the selection of flow from angle of up to 180°.

Body and output DISS in matt chromed brass, control regulation in polyamide, outer and inner tube in polycarbonate, stainless steel ball. Latex-free.

The flowmeters **selector** have been designed for saving of time and O₂. For when you need to connect a nebulizer or supply of oxygen without humidifying, have a control rotary that allows switching between the direct output to the face mask, nebulizer or humidifier, without interrupt the supply of O₂ during this operation.

Technical characteristics

	Oxyl	Oxyl selector	Oxyl dual
Dimensions	27 X 148 mm	63 x 154 mm	135 X 148 mm
Weight	164 g	210 g	504 g
Gas options	O ₂ and Air		
Outgoing connection	DISS O ₂ 9/16" - 18 UNF (selector : also outlet for pipe O ₂ 6 mm)		
Inlet pressure	4.5 ± 0.5 bar / 65 ± 0.7 psi / 450 ± 50 kPa		
Scales from L/min	0-5 0-15 0-30 0-70		



Oxyl

- 4540010 0-5 L/min
- 4540000 0-15 L/min
- 4540030 0-30 L/min
- 4540007 0-70 L/min



Oxyl selector

- 4540602 0-5 L/min
- 4540600 0-15 L/min
- 4540630 0-30 L/min
- 5540603 0-70 L/min

Configurable combinations of flowmeters with scales:
0-5 L/min, 0-15 L/min, 0-30 L/min and 0-70 L/min



Oxyl dual 4540005



Oxyl Rail 5450000



- 4540600
- +
- 5530000
- +
- 0930005

Perflow[®]

These flowmeters provide greater comfort and safety against accidental flow changes thanks to their whole design calibrated with high precision and "click" control. Selected flow indicator window of large diameter and high visibility.

The flowmeters have been designed to save time and O₂. For when a nebulizer or oxygen supply needs to be connected without humidification, have a rotary control that allows switching between the direct outlet to the face mask, nebulizer device or to the humidifier, without interrupting the supply of O₂ during this operation. Matt chrome-plated aluminium body, ABS control, DISS, outlet in matt chromed brass. Latex-free.

Perflow P4 y P5



- P4 4 bar
- P5 50 psi

Fixed inlet pressure

P4 y P5 selector



Perflow multy y multy selector



- Multy Variable inlet pressure
- Multy selector 2.8 - 7 bar 40 - 100 psi

It incorporates a pressure stabilizing micro-regulator that ensures the accuracy of the flow rate in the event of variations in the inlet pressure.

Flow ranges*

	0-1 L/min	0	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.5	0.6	0.7	0.8	0.9	1
OX1	0-1 L/min	0	0.1	0.15	0.2	0.25	0.3	0.35	0.4	0.5	0.6	0.7	0.8	0.9	1
OX5	0-5 L/min	0	0.1	0.2	0.3	0.4	0.6	0.8	1	1.5	2	2.5	3	4	5
OX15 / AIR15	0-15 L/min	0	0.2	0.5	0.7	1	1.5	2	3	4	5	7	10	12	15
OX50 / AIR50	0-50 L/min**	0	1	3	5	7	10	15	20	25	30	35	40	45	50
OX5 SELECTOR	0-5 L/min	0	0.1	0.2	0.3	0.4	0.6	0.8	1	1.5	2	2.5	3	4	5
OX15 SELECTOR	0-15 L/min	0	0.2	0.5	0.7	1	1.5	2	3	4	5	7	10	12	15

* Calibrated flows at STP conditions (23° C - 101.3 kPa)

** The flowmeter Perflow* 0-50 L/min is suitable for CPAP

Perflow P4 air



Perflow P4 dual



Perflow multy rail



Technical characteristics

	P4 and P5	Selector P4 and P5	Multy	Multy Selector
Dimensions	37 x 56 mm	38 x 79 mm	38 x 65 mm	38 x 88 mm
Weight	98 g	190 g	112 g	200 g
Gas options	O ₂ and Air			
Outgoing connection	DISS O ₂ 9/16" - 18 UNF			

Calibrated flowmeters



L/min	SS8752430	BS 5682	NF 90 116	Oxifar B	DIN 13260	DISS
O₂						
P4 OX15	5540801	5540803	5540804	5540806	5540807	5540810
Rail	5450801	5450803	5450804	5450806	5450807	5450809
P4 selector OX15	5540701	5540703	5540704	5540706	5540707	5540709
P4 OX15 dual	5542801	5542803	5542804	5542806	5542807	5542809
Rail	5452801	5452803	5452804	5452806	5452807	5452809
P4 OX50	5540811	5540813	5540814	5540816	5540817	5540819
Rail	5450811	5450813	5450814	5450816	5450817	5450819
P4 OX50 dual	5542811	5542813	5542814	5542816	5542817	5542819
P5 OX15						5540889
Rail						5450889
P5 selector OX15						5540789
P5 OX50						5540889
Rail						5450889
multy OX1	5540841	5540843	5540844	5540846	5540847	5540849
Rail	5450841	5450843	5450844	5450846	5450847	5450849
multy OX5	5540851	5540853	5540854	5540856	5540857	5540859
Rail	5450851	5450853	5450854	5450856	5450857	5450859
multy selector OX5	5540751	5540753	5540754	5540756	5540757	5540759
multy OX5 dual	5542851	5542853	5542854	5542856	5542857	5542859
multy OX15	5540861	5540863	5540864	5540866	5540867	5540868
Rail	5450861	5450863	5450864	5450866	5450867	5450869
multy selector OX15	5540761	5540763	5540764	5540766	5540767	5540769
multy OX15 dual	5542861	5542863	5542864	5542866	5542867	5542869

Air

P4 AIR15	5540821	5540823	5540824	5540826	5540827	5540829
Rail	5450821	5450823	5450824	5450826	5450827	5450829
P4 AIR50	5540831	5540833	5540834	5540836	5540837	5540839
Rail	5450831	5450833	5450834	5450836	5450837	5450839
P5 AIR15						5540898
Rail						5450898
P5 AIR50						5540899
Rail						5450899
multy AIR15	5540871	5540873	5540874	5540876	5540877	5540879
Rail	5450871	5450773	5450874	5450876	5450877	5450879

Special connections available on request: Chemetron, Ohmeda, Puritan, UNI, AFROX, ENV 737-6